

# PAC 3000

## WASHER HOSE

PRESSURE WASHER CLEANING HOSE

### PRODUCT INFORMATION

#### 1 Construction:

**Tube** - Seamless black synthetic rubber, oil and heat resistant

**Reinforcement** - one braid of high tensile steel wire

**Cover** - black, oil, abrasion and weather resistant synthetic rubber, MSHA approved  
 - -06 available in non-marking yellow or blue

**Finish** - -04, -06 - smooth cover; -08 - wrapped cover

#### 2 Temperature Range: -40° to +200°F, -40° to +93.3°C

#### ENGLISH DIMENSIONS

HOSE DASH SIZE	INSIDE DIAMETER (IN.)	OUTSIDE DIAMETER (IN.)	REINFORCEMENT	MAXIMUM WORKING PRESSURE (PSI)	MINIMUM BURST PRESSURE (PSI)	MINIMUM BEND RADIUS (IN.)	WEIGHT (LBS./FT.)
-04	.258+/-0.016	.532+/-0.023	1 WIRE	3,000	12,000	4.0	.17
-06	.384+/-0.014	.688+/-0.022	1 WIRE	3,000	12,000	4.5	.24
-08	.508+/-0.023	.812+/-0.032	1 WIRE	3,000	12,000	7.0	.32

#### METRIC DIMENSIONS

HOSE DASH SIZE	INSIDE DIAMETER (MM)	OUTSIDE DIAMETER (MM)	REINFORCEMENT	MAXIMUM WORKING PRESSURE (BAR)	MINIMUM BURST PRESSURE (BAR)	MINIMUM BEND RADIUS (MM)	WEIGHT (KG/M)
-04	6.6+/-0.4	13.5+/-0.6	1 WIRE	207	827	102	.25
-06	9.6+/-0.4	17.5+/-0.5	1 WIRE	207	827	114	.36
-08	12.9+/-0.6	20.6+/-0.8	1 WIRE	207	827	178	.48



600 S. SIOUX BLVD.  
 P.O. BOX 800  
 BRANDON, SD 57005

PHONE: (605) 582-7221  
 FAX: (605) 582-7222  
 WATS: 1-800-827-1610