

STARFLEX R17

HYDRAULIC HOSE

MEETS OR EXCEEDS REQUIREMENT FOR SAE J517-100R17

Compact wire braid hydraulic hoses have been increasingly used in many hydraulic applications over the recent years. Hoses of this type are smaller in diameter than one and two braid hoses with similar performance characteristics specified in SAE100 R1 & R2 which gives them the ability to operate at smaller bend radii. They are also lighter in weight and their compactness offers advantages when minimal space is available in installations.

Construction: Synthetic rubber black tube; one or two high tensile steel wire compact braid reinforcement; synthetic rubber black outer cover. Oil, fuel, weather, ozone and abrasion resistant. *Additional cover material options below.

Application: Medium pressure service with high temperature petroleum base hydraulic fluids, hot oil, grease, lubricant, and crude oils, air and water.

Temperature Range: -40°C to +100°C (-40°F to +212°F) constant operation.

SPECIFICATIONS

HOSE DASH SIZE	INSIDE DIAMETER IN (MM)	OUTSIDE DIAMETER IN (MM)	REINFORCEMENT	MAXIMUM WORKING PRESSURE PSI (BAR)	MINIMUM BURST PRESSURE PSI (BAR)	MINIMUM BEND RADIUS IN (MM)	WEIGHT LB/FT (KG/M)
-04	1/4 (6.4)	0.49 (12.5)	1 WIRE	3000 (207)	12000 (827)	2.0 (50)	0.13 (0.19)
-06	3/8 (9.5)	0.65 (16.5)	1 WIRE	3000 (207)	12000 (827)	2.5 (65)	0.18 (0.27)
-08	1/2 (12.7)	0.78 (19.7)	1 WIRE	3000 (207)	12000 (827)	3.5 (90)	0.31 (0.46)
-10	5/8 (15.9)	0.95 (24.0)	2 WIRE	3000 (207)	12000 (827)	4.0 (105)	0.38 (0.57)
-12	3/4 (19.0)	1.10 (28.0)	2 WIRE	3000 (207)	12000 (827)	5.0 (125)	0.52 (0.78)
-16	1.0 (25.4)	1.43 (36.2)	2 WIRE	3000 (207)	12000 (827)	6.0 (150)	0.94 (1.40)

Optional Cover Materials:

SEPMERROCK product line is a further improvement on our well know FLH product used in high abrasion environments. In addition to its recognized benefits of excellent resistance to ozone, UV radiation, high temperatures and salt water, it meets the special requirements of the underground coal mining industry.

SEPMERSHIELD products are characterized by excellent wear and ozone resistance which is achieved by the double-layer construction with rubber cover and an additional UHMW foil. Even after one million cycles, no measurable abrasion can be detected when tested according to EN ISO 6945. Approved by US-MSHA.



369 Elgin Street
PO Box 36
Brantford, ONT N3S 7P5
PHONE: (519) 756-8210
FAX: (519) 756-5961



700 E. Redwood Blvd
PO Box 800
Brandon, SD 57005
PHONE: (605) 582-7221
FAX: (605) 582-7222
TOLL FREE: 1-800-827-1610